

USE-RHH-RHW-2 ALUMINUM - 600V

DESCRIPTION:

Alan Wire type USE-RHH-RHW-2 conductors are primarily used in conduit or other recognized raceways for services and feeders as specified by the NEC (National Electric Code). USE-RHH-RHW-s is available in sizes ranging from #6 to 250MCM. The conductors are made with 8000 series aluminum alloy and cross-linked polyethylene insulation is applied.

STANDARDS AND SPECIFICATIONS:

- 600V Rated
- Wet/Dry Locations (90C)
- UL 44
- Sunlight Resistant
- Direct Burial Related
- UL 854
- 8000 Series Alloy
- Federal Spec JC-30B NEC

Conductor				Ampacity	
Size (AWG)	Stranding	Insulation Thickness	Nom. OD (Mils)	90° THHN/ THWN-2	Approx Net WT./MFT
6	7	60	0.292	60	49
4	7	60	0.339	75	66
2	7	60	0.388	100	94
1/0	19	60	0.507	135	152
2/0	19	80	0.538	150	182
3/0	19	80	0.592	175	219
4/0	19	80	0.637	205	270
250	37	95	0.714	230	322



830 South West Street / Sikeston, MO 63801
800.325.8050 / F: 800.622.3355