

# BARE COPPER SOLID

## DESCRIPTION:

Bare Copper conductors are primarily used for grounding purposes as specified in the National Electrical Code. Alan Wire Bare Copper conductors are normally annealed (soft) copper, solid or stranded. Medium-hard drawn tempers are also available in solid and stranded. Sizes 14 thru 2 are available in solid. Sizes 8 thru 2 are available in 7 strand. Sizes 1 thru 4/0 are available in 7 strand and 19 strand. 250 MCM, 350 MCM, and 500 MCM are available in 37 strand only. 600 MCM and 750 MCM are available in 61 strand only.

## STANDARDS AND SPECIFICATIONS:

- B-1 (Hard Drawn)
- B-2 (Medium Hard Drawn)
- B-3 (Soft or Annealed)
- REA/RUS Approved
- RoHS Compliant
- ARRA 2009 Section 1605  
"Buy American" Compliant

Size (AWG)	Stranding	Bare WT./MFT	Footage Per 25lb Spool	Spools Per Box
14	Solid	12.4	2000	2
12	Solid	19.8	1250	2
10	Solid	31.5	800	2
8	Solid	50.0	500	4
6	Solid	79.5	315	4
4	Solid	126.3	200	4
2	Solid	200.9	125	2



830 South West Street / Sikeston, MO 63801  
800.325.8050 / F: 800.622.3355